


# Downlights



Downlight 10cm 9W



Downlight 12cm 15W



Downlight 14cm 18W



Downlight 20cm 20W



Downlight 25cm 40W



CCT switch

Connection L-N-PE	CRI >80	Operating temp. -20~+40°C	Power factor >0,9	Lifespan 50.000h t <sup>9</sup> =25°C
----------------------	------------	------------------------------	----------------------	--

		Reference	EAN Code	Cover / Material	Color Light	Luminous Flux	Lm/W Efficiency	Power	Beam Angle	Working voltage	LEDs	IP	Guarantee	Cutting diameter	Dimensions	Packing details								
10cm 9W	Cool	DL9CW3	8436546691808	White / Aluminum	5000K	650lm	72Lm/W	9W	110°	100-240 VAC 50~60Hz	10 NICHIA NF2W757	30	5 years	96mm	(Ø)110mm x (H)53mm 260Gr	36 uts/box (L)402mm x (W)401mm x (H)270mm 10,4Kg								
	Neutral	DL9NW3	8436546691815		4000K	650lm	72Lm/W																	
	Warm	DL9WW3	8436546691822		3000K	600lm	67Lm/W																	
12cm 15W	Cool	DL15CW4	8436546691839		5000K	1150lm	77Lm/W	15W			90°			220-240 VAC 50~60Hz	15 NICHIA NF2W757	44	5 years	122mm	(Ø)140mm x (H)60mm 440Gr	24 uts/box (L)440mm x (W)325mm x (H)310mm 11,6Kg				
	Neutral	DL15NW4	8436546691846		4000K	1150lm	77Lm/W																	
	Warm	DL15WW4	8436546691853		3000K	1100lm	73Lm/W																	
14cm 18W	CCT Changeable	DLI18CC6	8436546695288		6000K 4000K 3000K	1600lm	89Lm/W	18W Optional dimming	90°	220-240 VAC 50~60Hz		70 MTC/ RUNLITE 2835	44		5 years			135mm- 145mm	(Ø)165mm x (H)63mm 350Gr	20 uts/box (L)510mm x (W)410mm x (H)410mm 10Kg				
20cm 20W	CCT Changeable	DLI20CC8	8436546695295		6000K 4000K 3000K	2050lm	103Lm/W	20W Optional dimming													80 MTC/ RUNLITE 2835	192mm- 210mm	(Ø)230mm x (H)75mm 700Gr	10 uts/box (L)680mm x (W)530mm x (H)280mm 9Kg
					6000K 4000K 3000K	4000lm	100Lm/W	40W Optional dimming																
25cm 40W	CCT Changeable	DLI40CC10	8436546695301		6000K 4000K 3000K	4000lm	100Lm/W	40W Optional dimming	154 MTC/ RUNLITE 2835	240mm- 255mm	(Ø)279mm x (H)94mm 900Gr	10 uts/box (L)720mm x (W)640mm x (H)330mm 11Kg												