

# Integral fixture



Linkable 10 units	WF 2	IP 65	CRI >80	Operating temp. -20~+45°C	Power factor >0,9	Lifespan 52.000h t <sup>a</sup> =25°C
----------------------	---------	----------	------------	------------------------------	----------------------	--

	Reference	EAN Code	Cover / Material	Color Light	Luminous Flux	Lm/W Efficiency	Power	Beam Angle	Working voltage	Connection	LEDs	Guarantee	Dimensions	Packing details	
60cm	Cool White	FX615CW2	Milky / PMMA+ Polycarbonate	5000K	2200lm	147Lm/W	15W	100°	85-265 VAC 50~60Hz	L-N (SoftConnect up to 10 units)	192 HONGLITRONIC 2835	5 years	(L)640mm (W)124mm (H)43mm 1,2Kg	6uts/box (L)705mm (W)285mm (H)161mm 7,2Kg	
	Neutral White	FX615NW2		4000K	2200lm	147Lm/W									
	Warm White	FX615WW2		8436546694564	3000K	2100lm									140Lm/W
120cm	Cool White	FX230CW2		5000K	4200lm	140Lm/W	30W				264 HONGLITRONIC 2835		(L)1200mm (W)124mm (H)43mm 2,3Kg	(L)1562mm (W)285mm (H)161mm 13,8Kg	
	Neutral White	FX230NW2		8436546694533	4000K	4200lm									140Lm/W
	Warm White	FX230WW2		8436546694571	3000K	4100lm									137Lm/W
150cm	Cool White	FX540CW2		5000K	5800lm	145Lm/W	40W				384 HONGLITRONIC 2835		(L)1500mm (W)124mm (H)43mm 2,8Kg	6uts/box (L)1562mm (W)285mm (H)161mm 16,8Kg	
	Neutral White	FX540NW2		8436546694557	4000K	5800lm									145Lm/W
	Warm White	FX540WW2		8436546694588	3000K	5500lm									138Lm/W
	Cool White	FX550CW2	8436546694380	5000K	7200lm	144Lm/W	50W	384 HONGLITRONIC 2835	(L)1500mm (W)124mm (H)43mm 2,8Kg	6uts/box (L)1562mm (W)285mm (H)161mm 16,8Kg					
	Neutral White	FX550NW2	8436546695622	4000K	7200lm	144Lm/W									
	Warm White	FX550WW2	8436546695639	3000K	6900lm	138Lm/W									

2 mounting clips included

# Integral fixture with Emergency function



Battery 3Hours	WF 2	IP 65	CRI >80	Operating temp. -20~+45°C	Power factor >0,9	Lifespan 52.000h t <sup>a</sup> =25°C
-------------------	---------	----------	------------	------------------------------	----------------------	--

		Reference	EAN Code	Cover / Material	Color Light	Standard Output	Emergency Output	Standard Power	Emergency Power	Beam Angle	Working voltage	Conne- ction	LEDs	Guaran- tee	Dimensions	Packing details
60cm	Cool	FX615CWE	8436546695035	Milky / PMMA+ Polycarbo- nate	5000K	2200lm	650lm	15W	7W	100°	85-265 VAC 50~60Hz	L-N	192 HONGLITRONIC 2835	5 years	(L)640mm (W)124mm (H)43mm 1,2Kg	6uts/box (L)705mm (W)285mm (H)161mm 7,2Kg
	Neutral	FX615NWE	8436546695042		4000K	2200lm	650lm									
	Warm	FX615WWE	8436546695059		3000K	2100lm	650lm									
120cm	Cool	FX230CWE	8436546695004		5000K	4200lm	650lm	30W	7W				264 HONGLITRONIC 2835		(L)1200mm (W)124mm (H)43mm 2,3Kg	(L)1262mm (W)285mm (H)161mm 13,8Kg
	Neutral	FX230NWE	8436546695011		4000K	4200lm	650lm									
	Warm	FX230WWE	8436546695028		3000K	4100lm	650lm									
150cm	Cool	FX540CWE	8436546694977		5000K	5800lm	650lm	40W	7W				384 HONGLITRONIC 2835		(L)1500mm (W)124mm (H)43mm 2,8Kg	(L)1562mm (W)285mm (H)161mm 16,8Kg
	Neutral	FX540NWE	8436546694984		4000K	5800lm	650lm									
	Warm	FX540WWE	8436546694991		3000K	5500lm	650lm									
	Cool	FX550CWE	8436546695127		5000K	7200lm	650lm	50W	7W				384 HONGLITRONIC 2835		(L)1500mm (W)124mm (H)43mm 2,8Kg	(L)1562mm (W)285mm (H)161mm 16,8Kg
	Neutral	FX550NWE	8436546695646		4000K	7200lm	650lm									
	Warm	FX550WWE	8436546695653		3000K	6900lm	650lm									

2 mounting clips included