

Surface luminaires



Surface 9W



IP65 + Sensor 12W



Sensor + Emergency 15W

15W Emergency Battery 3Hours	12W and 15W Motion sensor	CRI >80	Operating temp. -20~+45°C	Power factor >0,9	Lifespan 50.000h t ^a =25°C
------------------------------------	------------------------------	------------	------------------------------	----------------------	--

		Reference	EAN Code	Cover / Material	Luminous Flux (Emergency function)	Lm/W Efficiency	Power (Emergency function)	Beam Angle	Working voltage	Sensor	LEDs	IP	Guarantee	Dimensions	Packing details
Surface 9W	3000K	SSPWW9	8436546691518	White / Aluminum + PMMA	900lm	100Lm/W	9W	88°	100-240VAC 50~60Hz	X	36 SAMSUNG LM561B	20	3 years	(Ø)123mm (H)120mm 900Gr	12 uts/box (L)390mm (W)260mm (H)260mm 13Kg
IP65 + Sensor 12W	5000K	SL12CWSD	8436546694878	White / Polycarbonate	950lm	79Lm/W	12W	120°	220-240VAC 50~60Hz	✓	60 EPISTAR 2835	65		(L)280mm (W)132mm (H)93mm 800Gr	5 uts/box (L)595mm (W)585mm (H)320mm 15Kg
	4000K	SL12NWSDE	8436546694793		950lm	79Lm/W								(L)280mm (W)132mm (H)93mm 800Gr	5 uts/box (L)595mm (W)585mm (H)320mm 15Kg
	3000K	SL12WWSDE	8436546694885		850lm	71Lm/W								(L)280mm (W)132mm (H)93mm 800Gr	
Sensor + Emergency 15W	5000K	SL15CWSDE	8436546694892	White / Polycarbonate	1050lm (250lm)	70Lm/W	15W (3,5W)	120°	100-240VAC 50~60Hz	✓	72 EPISTAR 5050	44		(Ø)299mm (H)102mm 1200Gr	5 uts/box (L)635mm (W)325mm (H)335mm 5,3Kg
	4000K	SL15NWSDE	8436546694786		950lm (220lm)	63Lm/W									
	3000K	SL15WWSDE	8436546694908		850lm (200lm)	57Lm/W									