

# Track lights



TSE25



TSE40

Connection 3N	IP 20	CRI >90	Operating temp. -20~+40°C	Power factor >0,9	Lifespan 30.000h t <sup>a</sup> =25°C
------------------	----------	------------	------------------------------	----------------------	--

		Reference	EAN Code	Cover / Material	Color Light	Luminous Flux	Lm/W Efficiency	Power	Beam Angle	Working voltage	Connection	LEDs	Guarantee	Dimensions	Packing details
TSE25	Neutral White	TSE25NWW	8436546693499	White / Aluminum	4000K	2100lm	82Lm/W	25W	24°	100-240 VAC 50~60Hz	3-Phase	1 BRIDGELUX (COB)	3 years	(L)266mm (H)140mm 1Kg	20 ut/box (L)550mm x (W)360mm x (H)466mm 20,7Kg
	Warm White	TSE25WWW	8436546693505		3000K	2000lm	80Lm/W								
TSE40	Neutral White	TSE40NWW	8436546693635		4000K	3600lm	90Lm/W	40W	24°	100-240 VAC 50~60Hz	3-Phase	1 BRIDGELUX (COB)		(L)275mm (H)150mm 1,3Kg	8 ut/box (L)600mm x (W)570mm x (H)250mm 13Kg
	Warm White	TSE40WWW	8436546693642		3000K	3400lm	85Lm/W								