



LED Tri-proof model FX550NW2 branded SilverSun, 150cm length and beam angle 100°. White PVC body and milky polycarbonate diffuser. Colour temperature 4000K, luminous flux 7.200lm, color rendering index >80, power 50W, 85-265VAC / 50-60Hz and protection index IP65. Dimensions length 1500mm x width 124mm x height 43mm and weight 2,8 Kg. Mounting clips included. Light source with energy efficiency class E

LUMINOUS DATA

Luminous flux	7.200 lm
Efficiency	140 lm/W
Flux ErP Øuse (360°)	5850 lm
Colour rendering index CRI	≥80
Colour temperature	4.000K
Colour chromatic (sdcM)	1,8

ELECTRICAL DATA

Power	50W
Rated voltage	85-265V AC
Frequency	50/60Hz
Power factor	≥0,97
Harmonic distortion THD	<15%
Inrush current	43A
Max units per MCB C16	10
Dimmable	No
Flickering (Pst LM)	0,095
Max units linkable	10
Driver	Integrated
Class protection	Class II

OPTICAL DATA

Beam angle	100°
Diffuser model	Milky
Diffuser material	Polycarbonate

MECHANICAL DATA

Body material	PVC
Body colour	White RAL9016
IP protection rate	IP65
IK protection rate	IK08


FUNCTIONAL DATA

Working temperature	-20°C a 45°C
Lifespan (L70B10 25°)	>67.000h

LOGISTICAL DATA

EAN code	8436546695622
Device dimensions	1500x124x43mm
Device weight	2,8 kg
Units per box	6
Box dimensions	1562x285x161mm
Box weight	20 kg

DISTRIBUTION



DIMENSIONS

