



LED Aisle high bay model HBL200NW branded Silversun, length 92cm, beam angle 40°/100° and dimmable 1-10V. Grey aluminum body with polycarbonate optical lens diffuser. Colour temperature 4000K, luminous flux 32.000 lm, colour rendering index >80, power 200W, 220-240VAC/ 50-60Hz and protection indexes IP65 and IK10. Dimensions, length 924mm x width 256mm x height 110mm and weight 9,3 Kg. Suspension kit included.

LUMINOUS DATA

Luminous flux	32.000 lm
Efficiency	160 lm/W
Colour rendering index CRI	≥80
Colour temperature	4000K
Colour chromatic (sdcm)	1,0

ELECTRICAL DATA

Power	200W
Rated voltage	220-240V AC
Frequency	50/60Hz
Power factor	≥0,95
Harmonic distortion THD	≤10%
Inrush current	38,3A
Max units per MCB C16	8
Dimmable	1-10V
Driver	Internal
Class protection	Class I

OPTICAL DATA

Beam angle	40°-110°
Diffuser model	Optical Lens
Diffuser material	Polycarbonate

MECANICAL DATA

Body material	Aluminum
Body colour	Grey RAL7001
IP protection rate	IP65
IK protection rate	IK10


FUNCTIONAL DATA

Working temperature	-40°C a 50°C
Lifespan (L70B10 25°)	>250.000h

LOGISTICAL DATA

EAN code	8436546699262
Device dimensions	924x256x110mm
Device weight	9,3 kg
Units per box	1
Box dimensions	1085x320x180mm
Box weight	10,8 kg

DISTRIBUTION



DIMENSIONS

