



LED high bay model HBY200CWD branded Silversun, diameter 36cm, beam angle 90° and dimmable 1-10V. Black aluminum body with prismatic polycarbonate diffuser. Colour temperature 5000K, luminous flux 28.500 lm, colour rendering index >70, power 200W, 100-277 VAC/50-60Hz and protection index IP65. Dimensions, diameter 360mm x height 244mm, weight 4,7 Kg. Hanging hook included.

LUMINOUS DATA

Luminous flux	28.500 lm
Efficiency	142 lm/W
Colour rendering index CRI	≥70
Colour temperature	5000K
Colour chromatic (sdcm)	1,3

ELECTRICAL DATA

Power	200W
Rated voltage	100-277V AC
Frequency	50/60Hz
Power factor	≥0,98
Harmonic distortion THD	<20%
Inrush current	85A
Max units per MCB C16	7
Dimmable	1-10V
Driver	Built in
Class protection	Class I

OPTICAL DATA

Beam angle	90°
Diffuser model	Prismatic
Diffuser material	Polycarbonate

MECHANICAL DATA

Body material	Aluminum
Body colour	Black RAL9004
IP protection rate	IP65
IK protection rate	IK08


FUNCTIONAL DATA

Working temperature	-40°C a 50°C
Lifespan (L70B10 25°)	>250.000h

LOGISTICAL DATA

EAN code	8436546696124
Device dimensions	Ø360x244mm
Device weight	4,7 kg
Units per box	1
Box dimensions	440x440x310mm
Box weight	6 kg

DISTRIBUTION



DIMENSIONS

